

| SPECIFICATI   | <u>ONS</u>   |
|---|--------------|
| PERCENT OPEN AREA                                     | 79.6 %       |
| *WEIGHT PER SQ FT                                     | 0.989 lb     |
| **OPENING LIMITATION                                  | 1.100 inches |
| OVERALL THICKNESS                                     | 0.270 inches |
| ASPECT RATIO  | 1.00 : 1     |
| CRIMP STYLE   | 1313         |
| MAX <u>SIDE A</u> DIMENSION                           | 240 inches   |
| MAX SIDE B DIMENSION                                  | 96 inches    |
| AVAILABLE AL  | LOYS         |
| Stainless, Mild Steel, a<br>Bronze, Brass, Copper, Pr |              |

|     |   |   | NOTES |
|-----|---|---|-------|
| QTY | В | Α |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |
|     |   |   |       |



**Customization:** Alloy configurations and sheet dimensions may be customizable depending on project design. For more information on the manufacturing capabilities of this mesh, please contact us.

- \*\*Maximum sphere diameter which will pass through opening

Product specifications are subject to change. Product image is shown at 100% unless stated otherwise. For accuracy, specification sheet must be printed with no scaling. Measurements and data are approximate and should be confirmed with a physical sample.

